

200A Dual String Battery Cabinet

- 8 x 210Ahr Capacity Battery Cabinet
- Smart Solution for Limited Space Applications
- String or Stack Multiple Cabinets Together
- Complete with a 200A Main Breaker /Disconnect Installed
- Complete with Internal Battery Cabling Installed
- Complete with Insulation and Convection Cooling
- Supports Hidden Shackle Locks for Extra Security
- Optional Heater Pads and Thermostat Kit (-H)
- Optional Elevated Mounting Stand (-S)
- Optional 19" 8U Rack Adapters Available for Mounting Electronics



PTS8024-200X2

Electrical Specifications

| | |
|-----------------------------|--------------------------------------|
| DC Voltage | -48vDC Nominal |
| Internal Circuit Breaker | 200A (Other Values < 200A Available) |
| Maximum Battery Size | 210Ahr |
| Battery Positions | 8 |
| -48vDC Load Connection | 2-hole 5/16-18 with 1" Spacing |
| 0vDC Return Connection | 2-hole 5/16-18 with 1" Spacing |
| Enclosure Ground Connection | 2-hole 1/4-20 with 5/8" Spacing |

Mechanical Specifications

| | |
|--------------------------------|---------------------------------------|
| Housing Material | Powder Coated Aluminum |
| Enclosure Front Access | Padlockable Front Hatch |
| Enclosure Rear Access | Internally Secured Rear Hatch |
| Housing Dimensions (H x W x D) | 32.00 x 28.00 x 29.00 |
| Unit Weight / Shipping Weight | 105 lbs / 130 lbs |
| Stand Weight / Shipping Weight | 10 lbs / 20 lbs |
| Access | KO's Permitted Rear, Bottom and Sides |
| Operating Temp | -40 C to 75 C |
| Humidity | 100% Non-Condensing |



PTS8024-200X2-S



